

Smart Incubator AL01-07-100 for Research Labs

Features:

Incubator for all standard incubation experiments e.g. in microbiology labs and many more
Stainless steel interior equipped with 2 chrome-plated trays
Equipped with interior glass door
Microprocessor controller with large digital display of the temperature (decimal temperature displayed)
Build-in timer (0-999 mins) as alternative to continuous operation
Overtemperature protection with visible alarm (safety thermostat class 3.1)
Exhaust duct at rear of unit with manually adjustable slide
2 units are directly stackable using the flat assembly bars supplied with the units

Technical specification:

Size (liter):	115
Door:	Right Hinge
Trays:	2
Voltage(nominal +/-10%) 50Hz (V):	230
Temperature °C:	ambient +5 to 70
Air convection:	natural
Spatial temperature deviation °C:	± 0,7
Temperature accuracy °C:	± 0,2
Heating up time to 37°C:	71 mins (to of 98% of set temperature)
Recovery time 30 sec door open:	5 mins (to of 98% of set temperature)
Control Panel:	Automatic
Displays:	digital display of the temperature (Celsius or Fahrenheit) or timer
Safety thermostat:	mechanical class 3.1 with visible alarm
Temperature fuse:	class 1
Chamber Interior:	stainless steel
Exterior dimensions:	
Width*(mm):	820
Height*(mm):	760
Depth*(mm):	732
Interior dimensions:	
Width (mm):	600
Height (mm):	480
Depth (mm):	400
Weight incl. 2 trays	68 kg
Dimensions unit incl. packaging (WxHxD)	920 mm x 986 mm x 835 mm
Total weight incl. packaging	approx. 83 kg
Color:	cream white

*Dimensions refer to unit housing including unit feet, door hinge, controller panel and power cable kink protection. Please note: technical specifications refer to 25°C ambient temperature, 37°C set temperature and a mains voltage fluctuation of ± 10%. The temperature data are determined in accordance to DIN12880, part 2:2007.